



7-22 KW VARIABLE SPEED ROTARY SCREW COMPRESSORS

## LRS-Series

### Advanced Technology. Inspired Simplicity.

LRS-Series compressors from Gardner Denver feature more than just the latest compressor technology. They contain the cleanest, simplest, most intuitive machine layouts on the market. Equipped with standard TEFC main motors, robust and high performing Yaskawa inverter drives, GD Pilot™ microprocessor controllers and quiet enclosures, an LRS-Series unit from Gardner Denver is the optimal solution when a feature-rich, simple-to-operate compressor is required.

### First Class Serviceability

The LRS-Series units set a new standard in serviceability. By utilizing integrated airend design techniques, Gardner Denver delivers unprecedented access to service items such as; a high efficiency air filter, air/oil separator and oil filter. At the same time, the compact design eliminates unneeded connections and minimizes piping; reducing the opportunity for leaks. Couple these features with standard automatic belt tensioning and you have a world class small horsepower compressor package.

### Configuration Flexibility

LRS-Series compressors are available in base mount or AirStation™ configurations. The plug-and-play AirStation™ configuration is an LRS-Series compressor mounted on a horizontal receiver tank with or without a refrigerated air dryer. Featuring standard high-end and optional components such as a three-way bypass valve, stainless steel piping, integrated fork lift slots and an automatic tank drain, the LRS-Series AirStation™ is the ideal solution for a compressed air system that requires minimal installation time and cost.

**Gardner**  
**Denver**

# L07RS-L22RS ROTARY SCREW COMPRESSOR

MODEL	DRIVE MOTOR		50 Hz				60 Hz				WEIGHT		DIMENSIONS L x W x H IN. (MM)	
			NOMINAL PRESSURE		FAD <sup>1</sup>		NOMINAL PRESSURE		FAD <sup>1</sup>					NOISE LEVEL <sup>2</sup>
			PSIG	BAR	ACFM	M <sup>3</sup> /MIN	PSIG	BAR	ACFM	M <sup>3</sup> /MIN				DB(A) @ 70% LOAD
L07RS	10	7	100	7.0	44.5	1.26	110	7.0	42.9	1.22	63	489	222	27 x 25 x 41 (686 x 635 x 1041)
			130	9.0	35.7	1.01	130	9.0	37.6	1.07				
			190	13.0	29.3	0.83	190	13.0	27.9	0.79				
L11RS	15	11	100	7.0	63.9	1.81	110	7.0	62.1	1.76	64	509	231	
			130	9.0	55.1	1.56	130	9.0	56.9	1.61				
			190	13.0	44.5	1.26	190	13.0	43.5	1.23				
L15RS	20	15	100	7.0	91.8	2.60	110	7.0	92.0	2.61	67	805	365	
			130	9.0	77.0	2.18	130	9.0	81.3	2.30				
			190	13.0	59.0	1.67	190	13.0	59.1	1.67				
L18RS	25	18	100	7.0	107.7	3.05	110	7.0	107.8	3.05	68	840	381	31 x 28 x 47 (787 x 711 x 1194)
			130	9.0	92.5	2.62	130	9.0	95.7	2.71				
			190	13.0	77.7	2.20	190	13.0	77.8	2.20				
L22RS	30	22	100	7.0	125.0	3.54	110	7.0	125.2	3.55	69	851	386	
			130	9.0	111.2	3.15	130	9.0	116.3	3.29				
			190	13.0	93.9	2.66	190	13.0	94.0	2.66				

1) Data measured and stated in accordance with ISO1217, Ed. 4, Annex C & Annex E at the following conditions:

Air Intake Pressure 1 bar A, Air Intake Temperature 20° C, Humidity 0% (Dry)

2) Measured in free field conditions in accordance with ISO 2151, tolerance +/- 3dB

## AIR STATION SPECIFICATIONS, 60 HZ

MODEL	DRYER MODEL	RECEIVER SIZE GAL. (LITERS)	REFRIG-ERANT	WEIGHT LBS (KG)		DIMENSIONS L x W x H IN. (MM)	
				120 GAL	240 GAL	120 GAL	240 GAL
				L07RS	RNC50 GSRN50	80, 120, 240 (303, 454, 908)	R134A
L11RS	RNC75 GSRN75	Less Dryer 984 (447) With GSRN Dryer 1128 (512) With RNC Dryer 1090 (495)	Less Dryer 1362 (618) With GSRN Dryer 1506 (683) With RNC Dryer 1468 (666)	With Dryer 71 x 32 x 68 (1803 x 819 x 1722)	With Dryer 88 x 37 x 74 (2233 x 940 x 1875)		
L15RS	GSRN100 RNC100 RES90		Less Dryer 1306 (593) With GSRN Dryer 1572 (713) With RNC Dryer 1577 (715) With RES Dryer 1567 (711)	Less Dryer 1658 (752) With GSRN Dryer 1924 (873) With RNC Dryer 1929 (874) With RES Dryer 1919 (870)			
L18RS	GSRN125 RNC125 RES120	120, 240 (454, 908)	Less Dryer 1341 (608) With GSRN Dryer 1618 (734) With RNC Dryer 1634 (741) With RES Dryer 1619 (734)	Less Dryer 1693 (768) With GSRN Dryer 1970 (894) With RNC Dryer 1986 (901) With RES Dryer 1971 (894)	Less Dryer 72 x 32 x 72 (1838 x 819 x 1838) With Dryer 72 x 32 x 72 (1816 x 819 x 1838)	Less Dryer 90 x 37 x 78 (2276 x 940 x 1991) With Dryer 89 x 37 x 78 (2253 x 940 x 1991)	
L22RS	GSRN150 RNC150 RES140		Less Dryer 1352 (613) With GSRN Dryer 1639 (743) With RNC Dryer 1652 (749) With RES Dryer 1636 (742)	Less Dryer 1704 (773) With GSRN Dryer 1991 (903) With RNC Dryer 2004 (909) With RES Dryer 1988 (902)			

Dryer on AirStation™ package has separate electrical connection and voltage.

## LRS-Series Features (7-22 kW)

- Belt drive, oil flooded, single stage rotary screw air compressor
- AEON 4000 lubricant
- Air-cooled only
- Robust inverter drive
- Optional automatic zero-loss condensate drain (with receiver tank selection)
- CRN and ASME rated aftercooler
- Optional EMI filter and standard DC bus choke
- GD Pilot™ microprocessor controller
- Integrated thermostatic thermal mixing valve
- Integrated spin-on oil filter, spin-on air/oil separator and two-stage air filter
- IP54 electrical enclosure
- Moisture separator (shipped loose)
- Optional ASME receiver tank (80, 120, 240 gallons)
- Optional cold coalescing filter (with mounted RNC & RES dryers)
- Optional line reactor (shipped loose)
- Optional mounted cycling or non-cycling refrigerated dryer (with receiver tank selection)
- Quiet enclosure
- Standard manual tank drain (with receiver tank)
- TEFC main motor
- Optional three-way bypass valve (with receiver tank and mounted dryer)
- Second pressure band control for lead/lag operation
- Stainless steel piping (with receiver tank and mounted dryer)
- UL labeled electronics (including C-UL-US open industrial control panel)
- Voltage: 230V (3 phase only)  
380V (3 phase only)  
460V (3 phase only)  
575V (3 phase only)

# Gardner Denver®

Gardner Denver, Inc.

1800 Gardner Expressway

Quincy, IL 62305

866-440-6241

[www.gardnerdenver.com/gdproducts](http://www.gardnerdenver.com/gdproducts)



©2018 Gardner Denver, Inc. Printed in U.S.A.

GSCS-L07RS-L22RS 3rd Ed. 1/18